

Materials

54 - Melange Nap Fabric (REV.00) CAT. PLUS



54-241



54-411



54-441



54-521



54-651



54-711




54-751



54-791



54-911



54-951

54-Melange Nap is a woollen upholstery fabric distinguished by exceptional depth of colour and surprising details. It offers a distinctively unique melange expression. Extremely soft yet durable, Melange Nap appears to be brushed. It is constructed with a unicoloured and a melange yarn, that creates a graphic pattern of tiny

dots that play across its surface. The volume of details that emerge from the surface depends on the contrast between the yarns. Some of the darker colourways almost appear unicoloured whereas others have an intriguing multi-coloured look.

Composition: WV 97% - PA 3%

Weight: 440 gr lin. m

Width: 140 cm

Yarn type: Worsted

Pattern: Plain

Repeat: None

Care instructions:



| | | |
|-------------------------|--|----------------------------|
| Abrasion strenght | EN ISO 12947-2 | >100.000 cycles Martindale |
| Seam resistance | EN ISO 13936-1 | Warp 3,8mm / Weft 3mm |
| Sound absorption flat | EN ISO 354 | 0,55 - Class D |
| Sound absorption folded | EN ISO 11645 | 0,80 - Class B |
| Dry rub fastness | UNI EN ISO 105-X 12 | 4/5 Grey Scale |
| Wet rub fastness | UNI EN ISO 105-X 12 | 4/5 Grey Scale |
| Fastness to light | UNI EN ISO 105-B02 | 4/5 Grey Scale |
| Pilling resistance | EN ISO 12945-2 | 3/4 Pilling Scale |
| Fire reaction tests | BS 5852 Crib 5 with treatment / BS 5862 Part 3 / BS 5852 Source 1 California Technical Bulletin 117:2013 Section E Part 1 EN 1021 1-2 IMO FTP 8 Res. A652 NF D 60 013 Senate Bill (SB) 1019 UNI 9175 - CLASSE 1 EMME | |