

56 - Hallingdal Fabric (REV.00) CAT. PLUS



56-103



56-110



56-376



56-407



56-694



56-723



56-944

56-Hallingdal is a very durable upholstery fabric and is made of wool and viscose, which complement each other well: the wool provides excellent durability and flexibility, while the viscose adds brilliance

and depth to the colour. Both materials are dyed before they are spun, which highlights the rich texture of the fabric.

Composition: WV 70% - VI 30%
 Weight: 795 gr lin. m
 Width: 130 cm
 Yarn type: Woolen
 Pattern: Plain
 Repeat: None

Care instructions:



Abrasion strenght	EN ISO 12947-2	>100.000 cycles Martindale
Seam resistance	EN ISO 13936-1	Warp 4,5mm / Weft 4mm
Sound absorption flat	EN ISO 354	0,45 - Class D
Sound absorption folded	EN ISO 11645	0,70 - Class C
Dry rub fastness	UNI EN ISO 105-X 12	4/5 Grey Scale
Wet rub fastness	UNI EN ISO 105-X 12	3/4 Grey Scale
Fastness to light	UNI EN ISO 105-B02	5/7 Blue Scale
Pilling resistance	EN ISO 12945-2	3/4 Pilling Scale

Fire reaction tests

AS / NSZ 1530.3
 BS 5852 Crib 5 with treatment
 BS 5852 Part 3
 BS 5852 Source 1
 California Technical Bulletin 117:2013 Section E Part 1
 EN 1021 1-2
 IMO FTP 8 Res. A652
 NF D 60 013
 NFPA 260/UFAC
 Senate Bill (SB) 1019
 UNI 9175 - CLASSE 1 | EMME