

# Materials

## 60 - Sirio Fabric (REV.00) CAT. C



60-03



60-05



60-06




60-07




60-08




60-09



60-10



60-11



66-12

60-Sirio is made using a complex textile technique that allows the interweaving of threads of different sizes both in warp and in weft. This technique derives from the skillful and ancient technique of weaving carpets, in which a fine thread was used as a basic grid, and a larger

one as a color and design effect. This yarn features "flames", which create a three-dimensional appearance on the surface of the fabric together with a construction that recalls the classic "basketweave".

*Composition:*  
 VI 42% - CO 38% - PC 14% - PL 6%  
*Weight:* 720 +/- 5 gr/m<sup>2</sup>  
*Width:* 140 cm  
*Repeat:* None

Care instructions:



Abrasion strenght	EN ISO 12947-2	30.000 cycles Martindale
Dry rub fastness	UNI EN ISO 105-X 12	4/5 Grey Scale
Wet rub fastness	UNI EN ISO 105-X 12	4/5 Grey Scale
Fastness to light	UNI EN ISO 105-B02	5 Grey Scale
Pilling resistance	EN ISO 12945-2	3/4 Pilling Scale
Fire reaction tests	BS 5852 Source 0-1 Cigarette test / Match test California Technical Bulletin 117:2013 Section E Part 1 NFPA 260/UFAC Senate Bill (SB) 1019	