





C 101



C 86




C 85




C 89




C 83



C 100



C 84



C 88



C 87

technical specifications / specifiche tecniche



- COMPOSITION / COMPOSIZIONE  
54% New Zealand Wool  
44% Post-consumer recycled, polyester  
2% Polyamide
- ABRASION / ABRASIONE  
100.000 cycles, Martindale  
(EN ISO 12947-2)

- RUBBING FASTNESS /  
SOLIDITÀ ALLO SFREGAMENTO  
Dry and Wet 4-5, scale 1-5  
(EN ISO 105-X12:1995)
- PILLING  
4-5, scale 1-5 (EN ISO 12945-2)
- LIGHT FASTNESS / SOLIDITÀ ALLA LUCE  
5-7, scale 1-8 (EN ISO 105-B02)

- FLAME RESISTANCE  
RESISTENZA AL FUOCO  
BS EN 1021 1&2  
BS EN 1021-1  
ÖNORM A3800-1  
US CATB 117-2013 - Compliant  
to the criteria certifying the  
absence of flame retardant  
chemicals (AB 2998)

- APPROVED / OMOLOGATO






C 110




C 111




C 112



C 113




C 117




C 118




C 119




C 120




C 121



C 122



C 114



C 115



C 116

• APPROVED / OMOLOGATO



technical specifications / specifiche tecniche



- COLLECTION / COLLEZIONE  
**svensson - SEMI**
- COMPOSITION / COMPOSIZIONE  
85% Wool, 15% Polyamide
- ABRASION / ABRASIONE  
100.000 cycles,  
Martindale  
(EN ISO 12947-2)

- RUBBING FASTNESS  
SOLIDITÀ ALLO SFREGAMENTO  
Dry 4 and Wet 3-4,  
scale 1-5  
(EN ISO 105-X12)

- LIGHT FASTNESS  
SOLIDITÀ ALLA LUCE  
5-7, scale 1-8  
(EN ISO 105-B02)

- FLAME RESISTANCE /  
RESISTENZA AL FUOCO  
BS 5852 Crib 5  
EN ISO 1021 Part 1&2  
IMO FTP Code 2010:  
Part 8

UNI 9175 Classe 1 IM  
US CAT B 117-2013 - Compliant  
to the criteria certifying the  
absence of flame retardant  
chemicals (AB 2998)