



G 154



G 155




G 156




G 151



G 150



G 152



G 153


technical specifications / specifiche tecniche



- COLLECTION / COLLEZIONE  
**svensson** - BALANCE
- COMPOSITION / COMPOSIZIONE  
82% Wool  
12% Rami  
6% Polyamide
- ABRASION / ABRASIONE  
100.000 cycles, Martindale (EN ISO 12947-2)
- RUBBING FASTNESS / SOLIDITÀ ALLO SFREGAMENTO  
Dry 4 and Wet 3-4, scale 1-5  
(EN ISO 105-X12)
- LIGHT FASTNESS / SOLIDITÀ ALLA LUCE  
5-7, scale 1-8 (EN ISO 105-B02)
- FLAME RESISTANCE / RESISTENZA AL FUOCO  
BS 5852 Crib 5  
EN ISO 1021 Part 1&2  
IMO FTP Code 2010: Part 8  
UNI 9175 Classe 1 IM  
US CAT B 117-2013 - Compliant to the criteria certifying the absence of flame retardant chemicals (AB 2998)

- APPROVED / OMOLOGATO







G 59



G 192



G 69




G 190




G 193



G 194



G 195




G 75



G 66



G 71




G 64



G 61



G 63



G 73




G 62




G 70



G 191




G 72




G 67




G 78



G 196



G 197



G 68



G 65



G 74

technical specifications / specifiche tecniche



• COLLECTION / COLLEZIONE

**kvadrat**

G59+G69; G190+G197: STEELCUT TRIO

G70+G78: STEELCUT

DESIGNERS Dijkmeijer & Ridolfo

• COMPOSITION / COMPOSIZIONE

90% New wool

10% Nylon

• ABRASION / ABRASIONE

100.000 cycles; for G70+G78: 80.000 cycles  
Martindale (DS/EN ISO 12947-2:2016)

• PILLING

4, scale 1-5; for G70+G78: 3-4, scale 1-5  
(EN ISO 12945)

• LIGHT FASTNESS / SOLIDITÀ ALLA LUCE  
5-7, scale 1-8 (EN ISO 105-B02)

• SOUND ABSORPTION / ASSORBIMENTO ACUSTICO  
folded:  $\alpha_w = 0.95$  Class A  
for G70+G78: folded:  $\alpha_w = 0.80$  Class B  
(ISO 11654)

• FLAME RESISTANCE / RESISTENZA AL FUOCO  
AS/NZS 1530.3  
AS/NZS 3837 Class 2  
BS 5852 Part 1  
BS 5852 Crib 5 with treatment  
BS 5852 IGNITION SOURCE 3  
EN 1021 – 1/2  
GB 50222 B1 with treatment  
IMO FTP Code 2010: Part 8

NF D60-013

NFPA 260

ÖNORM B1/Q1

SN 198 898 5.3 with treatment


UNI 9175 Classe 1 IM

US CA TB 117-2013 - Compliant  
to the criteria certifying the  
absence of flame retardant  
chemicals (AB 2998)


• APPROVED / OMOLOGATO




PRODUCT CERTIFIED  
FOR LOW CHEMICAL  
EMISSIONS:  
UL CO 1000  
UL 2919  
170166-4.20




G 143




G 145




G 144




G 146



G 140



G 141



G 142

technical specifications / specifiche tecniche



- COLLECTION / COLLEZIONE  
**kvadrat** - RE-WOOL  
DESIGNER Margrethe Odgaard
- COMPOSITION / COMPOSIZIONE  
45% Recycled wool  
45% New wool  
10% Nylon
- ABRASION / ABRASIONE  
50.000 cycles, Martindale  
(DS/EN ISO 12947-2:2016)


- RUBBING FASTNESS / SOLIDITÀ ALLO SFREGAMENTO  
Dry and Wet 4-5, scale 1-5  
(ISO 105-X12)
- PILLING  
4, scale 1-5 (EN ISO 12945)
- LIGHT FASTNESS / SOLIDITÀ ALLA LUCE  
5-7, scale 1-8 (ISO 105-B02:2014)
- SOUND ABSORPTION / ASSORBIMENTO ACUSTICO  
folded:  $\alpha_w = 0.75$  Class C (ISO 11654)
- FLAME RESISTANCE / RESISTENZA AL FUOCO  
AS/NZS 1530.3  
AS/NZS 3837 Class 2

BS 5852 Part 1  
BS 5852 Crib 5 with treatment  
BS 5852 IGNITION SOURCE 3  
EN 1021 - 1/2  
IMO FTP Code 2010: Part 8  
NF D60-013  
ÖNORM B1/Q1  
UNI 9175 Classe 1IM  
US CA TB 117-2013 - Compliant to  
the criteria certifying the absence of  
flame retardant chemicals (AB 2998)


- APPROVED / OMOLOGATO




PRODUCT CERTIFIED  
FOR LOW CHEMICAL  
EMISSIONS:  
ULDO MDO  
UL 2818  
TV 166-420




G 170




G 171



G 172



G 173



G 174




G 175




G 176



G 210



G 211



G 212



G 213

technical specifications / specifiche tecniche



- COMPOSITION / COMPOSIZIONE  
96% Virgin Wool  
4% Polyamide
- ABRASION / ABRASIONE  
90.000 cycles, Martindale  
(DIN EN ISO 12947-2)
- PILLING  
4-5, scale 1-5 (EN ISO 12945-2)

- LIGHT FASTNESS / SOLIDITÀ ALLA LUCE  
5-8, scale 1-8 (EN ISO 105-B02)
- SOUND ABSORPTION / ASSORBIMENTO ACUSTICO  
folded:  $\alpha_w = 0.95$  Class A (ISO 11654)
- FLAME RESISTANCE / RESISTENZA AL FUOCO  
BS 5852:1979 (Part 1)  
BS 5852:2006 (Part 2) Crib 5  
DIN 4102-1 B2


EN 13501-1  
EN 1021 -1 and -2  
FAR 25.853 (12 sec. vertical)  
IMO: 2014/90/EU (MED)  
UNI 9175 Classe 11M  
US CAT B 117-2013 - Compliant  
to the criteria certifying the  
absence of flame retardant  
chemicals (AB 2998)

- APPROVED / OMOLOGATO






G 101



G 100



G 102

technical specifications / specifiche tecniche



• COLLECTION / COLLEZIONE

**kvadrat** - BASEL  
DESIGNERS Herzog & de Meuron

• COMPOSITION / COMPOSIZIONE

90% New wool  
10% Nylon

• ABRASION / ABRASIONE

50.000 cycles,  
Martindale (EN ISO 12947-2:1998)

• PILLING

4, scale 1-5 (EN ISO 12945)

• LIGHT FASTNESS / SOLIDITÀ ALLA LUCE

6-7, scale 1-8 (ISO 105-B02)

• FLAME RESISTANCE / RESISTENZA AL FUOCO

AS/NZS 3837 Class 2  
BS 5852 Part 1  
BS 5852 Crib 5 with treatment  
EN 1021 – 1/2  
GB 50222 B1 with treatment

IMO FTP Code 2010: Part 8

NFPA 260

NF D60-013

ÖNORM B1/Q1

SN 198 898 5.3 with treatment

UNI 9175 Classe 1 IM

US CA TB 117-2013 - Compliant

to the criteria certifying the

absence of flame retardant

chemicals (AB 2998)

• APPROVED / OMOLOGATO




PRODUCT CERTIFIED  
FOR LOW CHEMICAL  
EMISSIONS:  
IL COMMO  
II L 2816  
17016-6-420



G 120



G 121



G 122

technical specifications / specifiche tecniche



• COLLECTION / COLLEZIONE

**kvadrat** - MOLLY  
DESIGNER Åsa Pärson

• COMPOSITION / COMPOSIZIONE

100% New wool

• ABRASION / ABRASIONE

75-100.000 cycles,  
Martindale (EN ISO 12947-2:1998)

• PILLING

3-4, scale 1-5 (EN ISO 12945)

• LIGHT FASTNESS / SOLIDITÀ ALLA LUCE

6-7, scale 1-8 (ISO 105-B02)

• FLAME RESISTANCE / RESISTENZA AL FUOCO

BS 5852 Part 1  
BS 5852 Crib 5 with treatment  
EN 1021 - 1/2

IMO FTP Code 2010: Part 8

NFPA 260

NF D60-013

ÖNORM B1/Q1

UNI 9175 Classe 1IM

US CA TB 117-2013 - Compliant

to the criteria certifying the


absence of flame retardant

chemicals (AB 2998)

• APPROVED / OMOLOGATO



PRODUCT CERTIFIED  
FOR LOW CHEMICAL  
EMISSIONS:  
UL.COM/700  
UL 2215  
170166-420




G 130



G 131



G 132



G 133

technical specifications / specifiche tecniche



- COMPOSITION / COMPOSIZIONE  
95% Virgin Wool  
5% Polyamide
- ABRASION / ABRASIONE  
52.000 cycles, Martindale  
(DIN EN ISO 12947-2)
- PILLING  
4-5, scale 1-5 (EN ISO 12945-2)


- LIGHT FASTNESS / SOLIDITÀ ALLA LUCE  
5-8, scale 1-8 (EN ISO 105-B02)
- SOUND ABSORPTION / ASSORBIMENTO ACUSTICO  
folded:  $\alpha_w = 0.85$  Class B (ISO 11654)
- FLAME RESISTANCE / RESISTENZA AL FUOCO  
BS 5852:1979 (Part 1)  
BS 5852:2006 (Part 2) Crib 5  
DIN 4102-1 B2

EN 1021 -1 and -2  
EN 13501-1  
FAR 25.853 (12 sec. vertical)  
IMO: 2014/90/EU (MED)  
UNI 9175 Classe 1 IM  
US CA TB 117-2013 - Compliant  
to the criteria certifying the  
absence of flame retardant  
chemicals (AB 2998)

- APPROVED / OMOLOGATO







G 200




G 201




G 202




G 203



G 204



G 205



G 206

technical specifications / specifiche tecniche



• COLLECTION / COLLEZIONE

**kvadrat** - JAALI  
DESIGNER Doshi Levien

• COMPOSITION / COMPOSIZIONE

92% New wool  
8% Nylon

• ABRASION / ABRASIONE

80.000 cycles, Martindale  
(EN ISO 12947)

• RUBBING FASTNESS / SOLIDITÀ ALLO SFREGAMENTO

Dry 4-5 and Wet 3-5, scale 1-5  
(EN ISO 105-X12)

• PILLING

4, scale 1-5 (EN ISO 12945)

• LIGHT FASTNESS / SOLIDITÀ ALLA LUCE

6-7, scale 1-8 (EN ISO 105-B02)

• FLAME RESISTANCE / RESISTENZA AL FUOCO

AS/NZS 1530.3  
BS 5852 Part 1

BS 5852 Crib 5 with treatment

BS 5852 ignition source 3  
EN 1021-1/2

IMO FTP Code 2010: Part 8  
NF D60-013

SN 198 898 5.3 with treatment  
UNI 9175 Classe 11M

US CA TB 117-2013 - Compliant  
to the criteria certifying the  
absence of flame retardant  
chemicals (AB 2998)

• APPROVED / OMOLOGATO




PRODUCT CERTIFIED  
FOR LOW CHEMICAL  
EMISSIONS  
UL 2818  
P'0156-420




G 163



G 160



G 161




G 162




G 165



G 166



G 167



G 168



G 164



G 169

technical specifications / specifiche tecniche



• COLLECTION / COLLEZIONE  
**kvadrat** - HERO  
DESIGNER Patricia Urquiola

• COMPOSITION / COMPOSIZIONE  
96% New wool  
4% Nylon

• ABRASION / ABRASIONE  
45.000 cycles, Martindale  
(EN ISO 12947)

• PILLING  
3-4, scale 1-5 (EN ISO 12945)

- LIGHT FASTNESS / SOLIDITÀ ALLA LUCE  
5-7, scale 1-8 (ISO 105-B02)
- SOUND ABSORPTION / ASSORBIMENTO ACUSTICO  
folded:  $\alpha_w = 0.75$  Class C (ISO 11654)
- FLAME RESISTANCE / RESISTENZA AL FUOCO  
AS/NZS 3837 Class 2  
BS 5852 Crib 5 with treatment  
BS 5852 Part 1  
EN 1021 - 1/2  
IMO FTP Code 2010: Part 8  
IMO FTP Code 2010: Part 7 with treatment  
NF D60-013

SN 198 898 5.3 with treatment  
UNI 9175 Classe 1 IM  
US CA TB 117-2013 - Compliant  
to the criteria certifying the  
absence of flame retardant  
chemicals (AB 2998)

• APPROVED / OMOLOGATO




PRODUCT CERTIFIED  
FOR LOW CHEMICAL  
EMISSIONS:  
UL COMF00  
UL 2818  
170166-420




G 24




G 114




G 115




G 113




G 111



G 116




G 110




G 112



G 21



G 22



G 23

technical specifications / specifiche tecniche



- COLLECTION / COLLEZIONE  
**kvadrat**  
G110÷G116: DIVINA MD  
G21÷G24: DIVINA MELANGE  
DESIGNER Finn Skødt
- COMPOSITION / COMPOSIZIONE  
100% New Wool
- ABRASION / ABRASIONE  
45.000 cycles, Martindale  
(EN ISO 12947)
- PILLING  
3, scale 1-5 (EN ISO 12945)

- LIGHT FASTNESS / SOLIDITÀ ALLA LUCE  
5-7, scale 1-8 (ISO 105-B02)
- SOUND ABSORPTION / ASSORBIMENTO ACUSTICO  
folded:  $\alpha_w = 0.70$  Class C (ISO 11654)
- FLAME RESISTANCE / RESISTENZA AL FUOCO  
AS/NZS 1530.3  
BS 5852 Crib 5  
BS 5852 Part 1  
BS 5867 part 2 type B  
EN 1021-1/2  
EN 13501, C-s1, d0, glued  
GB 50222 B1 with treatment  
IMO FTP Code 2010: Part 8  
NF D60-013

NFPA 260  
ÖNORM B1/ Q1  
SN 198 898 5.3 with treatment  
UNI 9175 Classe 1 IM  
US CA TB 117-2013 - Compliant  
to the criteria certifying the  
absence of flame retardant  
chemicals (AB 2998)

- APPROVED / OMOLOGATO






G 225



G 220



G 221



G 222



G 223



G 224

technical specifications / specifiche tecniche



- COLLECTION / COLLEZIONE  
**kvadrat - SAHCC**  
MOSS  
DESIGNER Vincent Van Duysen
- COMPOSITION / COMPOSIZIONE  
52% Cotton  
22% Viscose  
14% Polyacrylic  
6% Linen  
3% Nylon  
3% Polyester

- ABRASION / ABRASIONE  
50.000 cycles, Martindale  
(EN ISO 12947)
- PILLING  
4-5, scale 1-5 (EN ISO 12945)
- LIGHT FASTNESS / SOLIDITÀ ALLA LUCE  
5-7, scale 1-8 (ISO 105-B02)

- FLAME RESISTANCE / RESISTENZA AL FUOCO  
BS 5852 crib 5 with treatment  
BS 5852 part 1  
EN 1021-1/2  
US CA TB 117-2013 - Compliant to  
the criteria certifying the absence of  
flame retardant chemicals (AB 2998)